

# Flip to Listen™

## DUAL MODE EARPLUGS



### HEAR WITHOUT REMOVING YOUR EARPLUGS

**Flip to Listen** are the first dual mode earplugs that not only protect wearers from noise but, with a quick **Flip**, also allow better communication when needed, without the inconvenience of removing earplugs.

### PROTECTION AND COMMUNICATION

The **Flip** cap allows you to easily switch from a closed position (NRR 24dB), for protection from continuous noise, to an open position (NRR 4dB), when you need to communicate or hear. Effective hearing protection for most noisy environments, plus the ability to hear more clearly away from the workplace. All without taking out your earplugs and having to refit them again.

### COMFORT ALL DAY LONG

**Flip to Listen** features a triple flange design that provides maximum comfort for all day wear. The soft flexible flanges provide a superior seal and fit most ear canals. The **Flip to Listen** stem helps you insert the earplug into the ear canal to get a good and secure fit, ready for protection and communication!

### REUSABLE CONVENIENCE AND COST SAVINGS

**Flip to Listen** earplugs can be easily washed and reused. Each pair comes with a Pocket-Pak® carrying case to keep them clean when not in use, plus an optional cloth cord.

### FEATURES:

- NRR 24 for most noisy environments.
- NRR 4 when you need to communicate or hear.
- No need to remove earplugs with **Flip** cap.
- Triple flange design provides all day comfort.
- Earplugs can be washed and reused.
- Pocket-Pak® carrying case provides hygienic storage of plugs between uses.
- Comes with optional cloth cord.
- All Moldex hearing protection is independently tested.
- 100% PVC-Free.

*Open cap to communicate or hear*



*Close cap for protection*



SKU Number: 6770

Authorized Distributor



Toll Free 888-972-3389  
sales@allsafeindustries.com



Closed Cap



Open Cap



**MOLDEX**  
Ideas that wear well.

## CAP CLOSED

### ATTENUATION DATA / DATOS DE ATENUACIÓN

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.

Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.

|   |      |      |      |      |      |      |      |      |      |                  |                  |
|---|------|------|------|------|------|------|------|------|------|------------------|------------------|
| Frequency (Hz)<br>Frecuencia (Hz)                   | 125  | 250  | 500  | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |                  |                  |
| Mean Attenuation (dB)<br>Datos de Atenuación (dB)   | 33.2 | 28.3 | 33.9 | 30.7 | 35.7 | 38.6 | 35.7 | 30.6 | 35.2 | NRR<br><b>24</b> | CSA<br><b>BL</b> |
| Standard Deviation (dB)<br>Desviación Estándar (dB) | 5.3  | 5.1  | 4.4  | 4.0  | 2.6  | 4.3  | 3.7  | 2.9  | 3.0  |                  |                  |

|  |           |                 |
|--|-----------|-----------------|
| <b>Noise Reduction Rating</b>  | <b>24</b> | <b>DECIBELS</b> |
| (WHEN USED AS DIRECTED)  |           |                 |
| THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS) |           |                 |
| MOLDEX-METRIC, INC. Flip to Listen<br>Culver City, CA #6770  |           |                 |
| Federal law prohibits removal of this label prior to purchase. <b>EPA</b> LABEL REQUIRED BY US EPA REGULATION 40 CFR PART 211 SUBPART B      |           |                 |

## CAP OPEN

### ATTENUATION DATA / DATOS DE ATENUACIÓN

Tested According to ANSI Specs S3.19-1974 by Michael & Assoc., State College, PA.

Probado de acuerdo a las especificaciones ANSI S3.19-1974 Michael & Assoc., State College, PA.

|   |     |      |     |      |      |      |      |      |      |                 |                 |
|---|-----|------|-----|------|------|------|------|------|------|-----------------|-----------------|
| Frequency (Hz)<br>Frecuencia (Hz)                   | 125 | 250  | 500 | 1000 | 2000 | 3150 | 4000 | 6300 | 8000 |                 |                 |
| Mean Attenuation (dB)<br>Datos de Atenuación (dB)   | 2.8 | -0.2 | 4.3 | 14.6 | 25.1 | 29.2 | 22.9 | 26.7 | 24.6 | NRR<br><b>4</b> | CSA<br><b>C</b> |
| Standard Deviation (dB)<br>Desviación Estándar (dB) | 2.6 | 1.7  | 2.9 | 2.5  | 4.9  | 2.8  | 3.4  | 3.3  | 4.0  |                 |                 |

|  |          |                 |
|--|----------|-----------------|
| <b>Noise Reduction Rating</b>  | <b>4</b> | <b>DECIBELS</b> |
| (WHEN USED AS DIRECTED)  |          |                 |
| THE RANGE OF NOISE REDUCTION RATINGS FOR EXISTING HEARING PROTECTORS IS APPROXIMATELY 0 TO 30. (HIGHER NUMBERS DENOTE GREATER EFFECTIVENESS) |          |                 |
| MOLDEX-METRIC, INC. Flip to Listen<br>Culver City, CA #6770  |          |                 |
| Federal law prohibits removal of this label prior to purchase. <b>EPA</b> LABEL REQUIRED BY US EPA REGULATION 40 CFR PART 211 SUBPART B      |          |                 |

**CLEANING INSTRUCTIONS:** Plugs should be routinely washed with mild soap and warm water.

**WARNING: Always wear with Cap Closed when used against hazardous noise levels.**

- Flip to Listen reusable earplugs must be fitted and worn correctly to provide effective protection. Reusable earplugs may deteriorate with use and should be examined for cracking or other deformations and replaced as necessary. Wash or clean hands before use. Plugs should be routinely washed with mild soap and warm water.  
CAUTION: Remove with a slow twisting motion to break the seal. Due to the tight seal, rapid removal may damage eardrum.
- Use these laboratory derived attenuation data for comparison purposes only. The amount of protection afforded in field use often is significantly lower depending upon how the protectors are fitted and worn.
- Failure to follow all instructions could result in hearing loss or injury. Failure to obtain a proper fit will reduce effectiveness of hearing protectors and could result in hearing loss or injury.
- Flip to Listen earplugs must only be used as part of a hearing conservation program that complies with applicable local safety and health regulations.
- Over protection can be dangerous. The wearer must be able to hear warning signals.
- Wearers with hearing loss should exercise extreme caution.
- It is the employer's responsibility to ensure that the type of hearing protector and its rating is appropriate for the user in their particular workplace.
- Use caution when working around machinery or any other equipment to ensure neck cord does not become caught or entangled.
- Failure to follow these warnings could result in serious injury or death.

### ORDERING INFORMATION

| SKU# | Contents/Bag                                  | Qty./Box         | Qty./Case        |
|------|---|------------------|------------------|
| 6770 | 1 Pair of Flip to Listen, cord and Pocket-Pak | 50 Pairs per Box | 4 Boxes per Case |

### MOLDEX-METRIC, INC.

10111 W. Jefferson Blvd., Culver City, CA 90232  
Tel: +1 (800) 421-0668 or +1 (310) 837-6500  
Fax: +1 (310) 837-9563  
Email: sales@moldex.com www.moldex.com

Moldex Technical Service Department:  
+1 (800) 421-0668 or +1 (310) 837-6500 Ext. 512/550

Moldex, Ideas that wear well, Pocket-Pak and the PVC-Free logo are registered trademarks. Flip to Listen is a trademark of Moldex-Metric, Inc. Made in U.S.A.

6770-035 REV B 10-13

**Step 1**  
Thread cord through hole #1.

**Step 2**  
Insert tip of cord into hole #2 to lock cord in place.

